



## PRODUCT DATA SHEET

PT1540

VERSION 3



### OVERVIEW

## 12 Gauge - Miscellaneous

Code: PT1540

Cal: 12 Gauge

Payload Weight: 1oz (28 grams)

**Cartridge, 12G, No.7 Shot  
(Waterproof)**

### SPECIFICATION

Payload: No. 7 Shot

Case Material: Aluminium

Operational Temperatures: -21°C to + 63°C

Safety Temperatures: -45°C to + 71°C

Accuracy: Minimum capability of 75% of the payload within an  
75cm target at 15 metres

Mean Chamber Pressures: 400 – 600 bar

Range: Up to 15m

Propellant Type: Double Base

Primer Type: Shotshell Primer

Weapon Capability: 3" chamber magnum proofed shotgun  
(true cylinder - unchoked)

### Description

The No.7 Bismuth Shot (Waterproof) has been designed for use in pump action shotguns.

The round has been developed to produce minimal FOD, making it ideal for use in areas such as airfields where foreign object damage is a major concern.

It is waterproof up to a depth of 10 metres, which contributes to its flawless operation in all kinds of weather.

Range Safety Template available on request.

### TRANSPORT & PACKAGING DETAILS

Packaging: M2A1

Dimensions mm: 306x156x192

Quantity Per Pack: 120

Gross Weight Nominal: 8.40kg

Maximum NEQ: 0.202kg

Proper Shipping Name: Cartridges for weapons, inert projectile

UN Serial Number: 0012

Hazard Class: 1.4S

Shelf Life: 5 years under controlled conditions

Storage requirements: To remain within original packaging, stored between +5°C to +30°C with a relative humidity not exceeding 70%.

Storage outside of these conditions will not be warranted and may reduce the shelf life and lead to the articles not functioning as intended.

Find out more

[sales@primetake.com](mailto:sales@primetake.com)

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.