

## PRODUCT DATA SHEET

PT4523B

VERSION 4

### OVERVIEW

## Distraction Device

Code: PT4523B

Weight: 105g

Distraction Device 1 Bang Training  
Reloadable Insert



### Description

This Distraction Device delivers lower outputs for exposure/safety. The report and light levels are optimised to train operators. No fragmentation, unit remains in one piece.

It is designed to be used in conjunction with Reusable Body PT4523BB.

When assembled to the Reusable Body it is bottom vented in order to discharge energy away from the hand of the operator.

### SPECIFICATION

Sound Output: 145 ±5dB

Light Output: 5,500,000cd Nominal

Delay Options: 0.5s or 1.0s

Operating Temperatures: -52° to 71°C

Dimensions: Overall Length 96mm

### TESTING

Environmentally Tested to MIL-STD-810G for:

Dust and Sand, Salt Fog, Driving Rain

Vibration Tested to MIL-STD-810G for:

Secured Cargo, Propeller Aircraft and Marine Vehicles

Flammability Tested:

Complies with Fire Safety Regulations 1988

No Ignition of Furnishings

Waterproof Tested: 15m for 3 hours

### TRANSPORT & PACKAGING DETAILS

Packaging: M2A1

Dimensions mm: 306x156x192

Qty per Outer Pack: 12

Gross Weight: 4.00kg

Maximum NEQ: 0.008kg (0.5s) / 0.011kg (1.0s)

Proper Shipping Name: Articles, pyrotechnic

UN Serial Number: 0432

Hazard Class: 1.4S

Service Life: 5 years under controlled conditions

Storage requirements: To remain with original packaging, stored between +5°C to +30°C with a relative humidity not exceeding 70%.

Storage outside of these conditions will not be warranted, may reduce the service life and lead to the device not functioning as intended.

Find out more

[sales@primetake.com](mailto:sales@primetake.com)

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.