



PRODUCT DATA SHEET

PT9100AC

VERSION 3



OVERVIEW

Pyro Trg-Sims

Code: PT9100AC

Friction Thunderflash Mk5

SPECIFICATION

Weight: 31.00g Approx

Length: 130mm

Diameter: 18mm

Net Explosive Content: 0.0065kg per article

Delay: 5s

Sound Level: 120dB @ 5m

Ignition: Friction

Methods of Use

The MK5 Friction Thunderflash is designed to simulate the functioning of a grenade or other similar event and should not be buried or fired on loose ground or gravel.

Description

The Pyrotechnic is held within a long thin tube with a removable head which has a small delay between initiation and event.

It is initiated by removing the top cap and using the element to strike the top of the main body, like striking a match.

TRANSPORT & PACKAGING DETAILS

Packaging: Fibreboard Box

Quantity Per Pack: 250

Gross Weight Nominal: 9.10kg

Maximum NEQ: 1.625kg

Proper Shipping Name: Articles, pyrotechnic

UN Serial Number: 0431

Hazard Class: 1.4G

Service Life: 3 years under controlled storage conditions

Find out more

sales@primetake.com

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.