

PRODUCT DATA SHEET

PT3510A

VERSION 3



OVERVIEW

12 Gauge - Breaching/Solid

Code: PT3510A

Cal: 12 Gauge

12G Low Power RAM Round

SPECIFICATION

Case Material: Green Plastic / Brass Ferrule

Operational Temperatures: -21°C to +63°C

Safety Temperatures: -45°C to +71°C

Mean Chamber Pressure: 400 bar approx.

Range: up to 1m

Propellant Type: Nitrocellulose

Primer Type: Shotshell Primer

Weapon Compatibility: 2¾" and 3" chamber magnum proofed shotgun (true cylinder - unchoked)

Description

The Low Power RAM Round is designed for use at close range (up to 1m) for the humane despatch of animals whilst providing minimal risk of over-penetration and ricochet to the handler.

The round contains a loosely filled payload of chalk and micronised stainless steel powder, which minimises the risk of ricochets and over-penetration.

Range safety template available on request.

TRANSPORT & PACKAGING DETAILS

Packaging: Fibreboard Box

Dimensions mm: 340x240x140

Quantity Per Outer Pack: 200

Gross Weight: 10.15kg

Maximum NEQ: 0.208kg

Proper Shipping Name: Cartridges, small arms

UN Serial Number: 0012

Hazard Class: 1.4S

Shelf Life: 5 years under controlled conditions

Storage requirements: To remain within original packaging, stored between +5°C to +30°C with a relative humidity not exceeding 70%.

Storage outside of these conditions will not be warranted and may reduce the shelf life and lead to the articles not functioning as intended.

Find out more

sales@primetake.com

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.