



## PRODUCT DATA SHEET

PT1006B

VERSION 10a



### OVERVIEW

## 12 Gauge - Distraction & Crowd Control

Code: PT1006B

Cal: 12 Gauge

Projectile Weight: 9 grams approx.

**12G BSC Shotgun - Long Range - Nitro**

### SPECIFICATION

Case Material: Red Plastic / Brass Ferrule

Projectile: Long Range projectile

Effective Range: 65 metres minimum

Recommended Firing Angle: 30°

Sound Level: 140dB average at 10m distance + 1m height\*

Propellant Type: Nitrocellulose

Primer Type: Shotshell Primer

Weapon compatibility: 2¾" and 3" Shotgun ONLY (true cylinder - unchoked)

### TRANSPORT & PACKAGING DETAILS

Packaging: M2A1

Dimensions [mm]: 306x156x192

Quantity Per Pack: 100

Gross Weight Nominal: 5.42kg

Maximum NEQ: 0.52kg

Packaging: Fibreboard Box

Dimensions [mm]: 340x240x140

Quantity Per Pack: 150

Gross Weight Nominal: 3.50kg

Maximum NEQ: 0.85kg

Proper Shipping Name: Articles, pyrotechnic

UN Serial Number: 0431

Hazard Class: 1.4G

Shelf Life: 5 years under controlled conditions

Storage requirements: To remain within original packaging, stored between +5°C to +30°C with a relative humidity not exceeding 70%.

### Description

The Long Range Nitro Shotgun Cartridge is designed to be used as a training aid or when a requirement to create a distraction at a distance is needed. It is also known as an Aerial Thunderflash.

The 12G Long Range Nitro Cartridge produces a smoke trail during flight with a loud report. The effective range achieved by Primetake's Long Range Nitro cartridge can vary between 50m and 80m, with the average being 65m.

Range Safety Template available on request. Environmental conditions at the time of firing, such as wind speed and direction, should always be considered - firing advice available on request.

\*Sound levels and range are variable and influenced by environmental conditions.

Find out more

[sales@primetake.com](mailto:sales@primetake.com)

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.