







PRODUCT DATA SHEET

PT1527A

VERSION 6



OVERVIEW

12 Gauge - Practice & Training

Code: PT1527A Cal: 12 Gauge

Cartridge, Shotgun, 12G, Irritant, Short Range, Practice, HP (Non Waterproof)

SPECIFICATION

Payload: Calcium carbonate / Refined Bismuth powder mix

Case Material: Blue Plastic / Brass Ferrule
Operational Temperatures: -21°C to +63°C

Safety Temperatures: -45°C to +71°C Penetration: 30-60 minute fire door Recommended Stand-Off: 25mm

Mean Chamber Pressure: 400 - 600 bar

Propellant Type: Double Based Nitrocellulose

Primer Type: Shotshell Primer

Weapon Compatibility: 3" chamber magnum proofed shotgun

(true cylinder - unchoked)

Description

The Short Range IMP (Irritant Multi Purpose) round is designed for use during training operations to simulate deployment of 'live' CS. It can be fired at close range, with a recommended stand-off distance of 25mm from the target and produces an immediate, large volume cloud of chalk particles up to 10 metres behind a barricade.

The round can be deployed against doors and windows with the ability to disrupt locks and hinges. It can also be deployed against soft skinned vehicles.

The round incorporates a loose filled payload mixture of chalk and refined Bismuth powder, which reduces the risk of ricochet and over penetration.

TRANSPORT & PACKAGING DETAILS

Packaging: M2A1 Packaging: Fibreboard Box

Dimensions mm: 306x156x192 Dimensions mm: 340x240x140

Qty per Outer Pack: 120 Qty per Outer: 200
Gross Weight: 9.77kg Gross Weight: 11.76kg
Maximum NEQ: 0.204kg Maximum NEQ: 0.34kg

Proper Shipping Name: Cartridges for weapons, inert projectile

UN Serial Number: 0012

Hazard Class: 1.4S

Shelf Life: 5 years under controlled conditions

Storage requirements: To remain within original packaging, stored between +5°C to +30°C with a relative humidity not

exceeding 70%.