

PRODUCT DATA SHEET

PT1508A

VERSION 6



OVERVIEW

Ceremonial/Saluting

Code: PT1508A

Powder Charge: 300g

Cartridge, 3Pdr Blank, 300g Charge

SPECIFICATION

Case Material: Anodised Aluminium (brass coloured)

Overall Length: 250mm

Operational Temperatures: -21°C to +49°C

Propellant Type: Black Powder

Primer Type: 0.50" cal Percussion Primer

Weapon Compatibility: 3Pdr Canon or equivalent

TRANSPORT & PACKAGING DETAILS

Packaging: Plywood Box

Dimensions: 500 x 280 x 320

Qty per Outer pack: 15

Gross Weight: 21.20kg approx.

Maximum NEQ: 4.51kg

Proper Shipping Name: Cartridges for weapons, blank

UN Serial Number: 0326

Hazard Class: 1.1C

Shelf Life: 5 years under controlled conditions

Storage requirements: Articles should remain within the original sealed packaging; within a temperature range of +5°C to +30°C where the relative humidity does not exceed 70%.

Storage outside of these conditions will not be warranted and may reduce the shelf life and lead to the articles not functioning as intended.

Description

The 3Pdr Blank is designed to be used for saluting and ceremonial purposes. The cartridge emits smoke and a loud report upon firing; without leaving any burning debris on the ground.

The cartridge design consists of an anodised aluminium, brass coloured two-piece case which houses a percussion primer in the base, used to ignite the black powder charge.

The Cartridge is designed to be fired through a 3Pdr Canon or equivalent.

Range Safety Template available on request.
Primetake's internal testing/ proofing methodology and weapon specification available on request.

Find out more

sales@primetake.com

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.