


4. DEMOLITION ACCESSORIES		
Safety Fuse L1A3	Catalogue No. 04.01.9504	Vers. 2
Primetake Part - PT9504		

<p>Methods of Use</p> <p>Primetake Safety Fuse is used in demolition work where a delay is required to give personnel time to retire to a place of safety before the charge detonates.</p>	
<p>Description</p> <p>The Safety Fuse consists of a train of gunpowder enclosed in yarn wrapped in a waterproof composition and protected by a black outer plastic covering.</p>	
<p>Performance/Safety</p> <p>The Safety Fuse has a burning speed of 131 +/- 13% seconds per metre and is supplied in either 8m lengths or 480m reels.</p>	

4. DEMOLITION ACCESSORIES

Safety Fuse L1A3

Catalogue No. 04.01.9504

Vers. 2

Primetake Part - PT9504

EXPLOSIVE TYPE

Black powder

EXPLOSIVE QUANTITY

5.6 grams per metre nominal

DIAMETER

4.95 to 5.20 mm

SHELF LIFE

3 years under controlled storage conditions

PROPER SHIPPING NAME

Fuse, safety

UN SERIAL No.

0105

HAZARD CLASS

1.4S

We constantly review our products – specifications are a guide and may vary so please check that the latest specification meets your requirements.



PRIMETAKE LTD.

Reepham Road, Fiskerton, Lincoln, LN3 4EZ, UK

Tel: +44 (0)1522 752323 Fax: +44 (0)1522 752484

Email: sales@primetake.com

